



## Act-O-Matic® Shower Head

# AC-11

### ► Description

Act-O-Matic®, Chrome Plated, Self-Cleaning Shower Head with Thumb Screw Volume Control.

### ► Flow Rate

2.5 gpm/9.4 Lpm maximum

### ► Specifications

Act-O-Matic, Chrome Plated Shower Head with the following features:

- Spring loaded, Self-Cleaning Spray Disk to prevent particle clogging
- "Cone-within-a-cone" Spray Pattern for total body coverage
- Pressure Compensating 2.5 gpm/9.4 Lpm Flow Control
- All Brass Construction
- Universal Ball Joint with Thumb Screw Volume Control
- 1/2" I.P.S. Inlet

Shower Head shall be in conformance to all requirements of ANSI/ASME Standard A112.18.1M, CSA B-125 and the United States Federal Energy Policy Act.

### ► Variations

- ☐ YC Spray Arm with Set Screw Flange

### ► Finishes

<input type="checkbox"/> PB	Polished Brass
<input type="checkbox"/> LG	Luster Gold (24k)
<input type="checkbox"/> AB	Antique Brass
<input type="checkbox"/> SF	Satin Finish

NOTE: Shower Head available with 1/2" Whitworth Thread (please specify).

See Accessories Section of the Sloan catalog for details on these and other Shower Head variations.

