

S P E C I F I C A T I O N S H E E T

Model: 40311C – 40314C – 40315C – 40316C series



A Moen Incorporated Brand



Trims for Pressure Balancing Cycling In-Wall Valve



DESCRIPTION

- Metal construction with chrome plated or LifeShine® Brushed Nickel finishes
- 40316C – valve only trim
- 40315C – shower only trim
- 40314C – tub/shower trim w/ IPS tub spout
- 40311C – tub/shower trim w/ slip fit tub spout
- Twelve (12) individual boxes per master carton

OPERATION

- Rotating style metal lever handle
- Temperature control by 150° arc
- Will operate with less than 5 lbs of torque
- Metal escutcheon features back printed polycarbonate overlay with red/blue international temperature marking
- Protective gaskets surround interior and exterior rim
- Weep hole located at bottom of escutcheon
- Slip fit tub spout connects to 1/2" pipe with bottom 5/32" set screw
- IPS tub spout connects to 1/2" mips pipe

FLOW

- Showerhead limited to 2.5 gpm (9.5 L/min) MAX

IN-WALL VALVE SOLD SEPARATELY

- 45311 CC/Male IPS with stops
- 45312 CC/Male IPS
- 45317 Female IPS with stops
- 45318 Female IPS
- 45319 PEX connections

STANDARDS

- Third party certified to CSA B125, ASME A112.18.1, ANSI A117.1, IAPMO, and all applicable requirements referenced therein, California Proposition 65, Illinois, Massachusetts, and Texas
- All CFG products are compliant to all plumbing codes that require 3rd party certification to the applicable plumbing/fitting standards
- Features red/blue hot/cold temperature indicators

WARRANTY – RESIDENTIAL, COMMERCIAL

- Ten (10) year limited warranty against defects in materials and manufacturing workmanship
- Refer to the installation instructions enclosed with each CFG product or call 1-888-450-4910 for complete warranty information

CRITICAL DIMENSIONS

