



# Specifications

### DESCRIPTION

- Metal construction with various finishes identified by suffix
- Flexible supply lines with 3/8" compression fittings
- Includes metal pop-up waste assembly

#### **OPERATION**

- Lever style handle
- Temperature controlled by 100° arc of handle travel
   FLOW
- Flow is limited to 1.5 gpm max (5.7L/min) at 60 psi **CARTRIDGE**
- 1255<sup>™</sup> Duralast<sup>™</sup> cartridge for Single-Handle Faucets **STANDARDS**
- Third party certified to ASME A112.18.1/CSA B125.1, NSF 61/9 and all applicable requirements referenced therein
- Contains no more than 0.25% weighted average lead content
  Third party certified to comply with WaterSense® High Efficiency
- Bathroom Sink Faucet Specification
  Complies with California Proposition 65 and with the Federal Safe Drinking Water Act

## ADA for lever handle

## WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original consumer purchaser
- 5 year warranty if used in commercial installations



RIZON™ Single-Handle Lavatory Faucet

## Model: 6900

**NOTE:** THIS FAUCET IS DESIGNED TO BE INSTALLED THRU 1 HOLE, 1-1/8" MIN. DIA.





