





Stainless Steel Technical Specification Robe Hook P1703

Dimensions: Stock Numbers: to compl IAPMO Green listed and third party certified for WaterSense **Envi™ Eco-Performance** P1703 - **VRXXIII DO APIO** VIK Stainless Stein implied warranty against leaks, drips and finish defects to the original consumer purchaser Concealed Sea war and finish defects to the original consumer purchaser 3-Function Showerhead Models: 3233EP series 3.875 GREEN Depth 3-1/2" (89mm) **Installation Instructions: Materials:** Robe Hook is stamped from Type Remove mounting bracket from back of fixture by loosening the set 304 stainless steel. Position unit on wall in desired location. Lightly mark the outline of the base of the unit. Center mounting bracket inside the outline. 5. Mark hole locations, Attach bracket to wall using 1 3/8" screws Mount base on bracket. Tighten set screw on the bottom. Note: Wood blocking is preferable behind all wall surfaces. If wood blocking is not available, the following optional fasteners are suggester Tie Maspine Ristors ead Anchors; Plaster/Drywall -Toggle Bolts. Cleaning Instructions: Rev. 2/11 To preserve the fine finish of this product, clean only with a softwww.moer damp cloth. Dry well. Do not use commercial or abrasive cleaners Stock Number: Robe Hook By Creative Specialties

