





Slimline® Bedpan BPW-1000 **Washer Model** Flushometer

Royal® Slimline® Bedpan Washer Water Closet Flushometer, for floor mounted or wall hung top spud bowls.

☐ Model BPW-1000-1.6 Low Consumption (1.6 gpf/6.0 Lpf) ☐ Model BPW-1000 Water Saver (3.5 gpf/13.2 Lpf)

Specifications

Quiet, Exposed, Diaphragm Type, Chrome Plated Closet Flushometer with the following features:

- Dual Filtered Bypass
- · Metal Oscillating Non-Hold-Open Handle with Triple Seal Handle Packing
- 1" I.P.S. Screwdriver Bak-Chek® Angle Stop
- · Free Spinning Vandal Resistant Stop Cap
- Adjustable Tailpiece
- · High Back Pressure Vacuum Breaker Flush Connection with Onepiece Bottom Hex Coupling Nut
- Spud Coupling and Flange for 1½" Top Spud
 Sweat Solder Adapter w/Cover Tube & Cast Wall Flange w/Set Screw
- Diaphragm, Handle Packing, Stop Seat and Vacuum Breaker molded from PERMEX™ rubber compound for Chloramine resistance
- 100% of the energy used in manufacturing is offset with Renewable Energy Sources Wind Energy

Bedpan Washer Diverter Assembly with the following features:

- Solid One-piece Body Construction
- Solid Brass Spray Arm
- · Counter Balanced Pivot Assembly
- · Diverter Valve Wall Support

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance to the applicable sections of ASSE 1037 and ANSI/ASME A112.19.2.

Variations

variatio	3113	
□ O	Offset Vacuum Breaker Specify: 1" - 11/2" - 2"	
□ YI	Two Wall Bumpers (for open front seat without cover)	
□ SG	SaniGuard® Antimicrobial Handle, Handle Socket and	

See Accessories Section of the Sloan catalog for details on these and other Flushometer variations.





