









Sloan Bedpan **Washer Model Flushometer**

BPW-1100

Description
Sloan* Bedpan Washer Water Closet Flushometer for floor mounted or wall hung top spud bowls. Installation meets ADA height requirements.

☐Model BPW 1100 Water Saver (3.5 gpf/13.2 Lpf)
☐Model BPW-1100-1.6 Low Consumption (1.6 gpf/6.0 Lpf)

□ DFB Dual Filtered Fixed Bypass Diaphragm

□ YI Two Wall Bumpers (for open front seat without cover)

Specifications

Quiet, Exposed, Diaphragm Type, Chrome Plated Closet Flushometer with the following features:

High Chloramine Resistant PERMEX™ Synthetic Rubber Diaphragm with Linear Filtered Bypass and Vortex Cleansing Action™
 ADA Compliant Metal Oscillating Non-Hold-Open Handle with Triple

Seal Handle Packing
1" I.P.S. Screwdriver Bak-Chek™ Angle Stop

Vandal Resistant Stop Cap Adjustable Tailpiece

Vacuum Breaker with Flush Connection

Spud Coupling and Spud Flange for 11/2" Top Spud

Sweat Solder Adapter with Cover Tube and Cast Wall Flange

High Copper, Low Zinc Brass Castings for Dezincification Resistance Non-Hold-Open Handle and No External Volume Adjustment to Ensure Water Conservation

Low Consumption flush accuracy
Handle Packing, Stop Seat and Vacuum Breaker Molded from
PERMEX™ Rubber Compound for Chloramine Resistance

Bedpan Washer Diverter Assembly with the following features:

Solid One-piece Body Construction

Solid Brass Spray Arm Counter Balanced Pivot Assembly

Diverter Valve Wall Support

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance to the applicable sections of ASSE 1037, ANSI/ASME 112.19.2, and Military Specification V-29193.

Contractor-friendly Packaging Installation time is reduced by packaging rough-in components and finishing components separately. In addition, all main valve components and subassemblies are factory assembled requiring less field assembly

of the valve on the job site. Components are packaged as follows:
 Stops and Supply Kits, packaged separately — 6 per package
 Fully assembled Valve, packaged with complete Vacuum Breaker Assembly and Flange Kit — 2 per package

See Accessories Section of the Sloan catalog for details on these and other Flushometer variations.

