

## DESCRIPTION

Complete HET system with Solar-Powered, Sensor Operated OPTIMA Plus® closet Flushometer and vitreous china water closet.

### Flush Cycle

Model WETS 2000.1201-1.28 SOLIS (1.28 gpf/4.84 Lpf)



## SPECIFICATIONS

Quiet, exposed, diaphragm type, chrome plated closet Flushometer for either left or right hand supply with the following features:

### Flushometer

- PERMEX® Synthetic Rubber Diaphragm with Dual Filtered Fixed Bypass
- Flex Tube Diaphragm designed for improved life and reduced maintenance
- ADA Compliant OPTIMA Plus® Solar-Powered Infrared Sensor for automatic "No Hands" operation
- Infrared Sensor with Multiple-focused, Lobular Sensing Fields for high and low target detection
- Latching Solenoid Operator
- Engineered Metal Cover with replaceable Lens Window
- Courtesy Flush™ Override Button
- Sensor assembly powered by a solar cell that will harvest power from artificial indoor light, either incandescent or fluorescent light, providing approximately 100% power with 650 illuminance (lux).
- Four (4) Size AA Battery back-up power source
- "Low Battery" Flashing LED
- Infrared Sensor Range Adjustment Screw
- Initial Set-up Range Indicator Light (first 10 minutes)
- Chrome Plated Metal Handle Cap
- 1" I.P.S. Screwdriver Bak-Chek® Angle Stop
- Free spinning, Vandal Resistant Stop Cap
- Adjustable Tailpiece
- High Back Pressure Vacuum Breaker Flush Connection with One-piece Bottom Hex Coupling Nut
- Spud Coupling and Flange for 1-1/2" Top Spud
- Sweat Solder Adapter w/Cover Tube and Cast Wall Flange w/Set Screw
- High copper, low zinc brass castings for dezincification resistance
- Fixed Metering Bypass and no external volume adjustment to ensure water conservation
- Flush Accuracy Controlled by CID® Technology
- Diaphragm, Stop Seat and Vacuum Breaker to be molded from PERMEX® rubber compound for chloramine resistance
- Valve Body, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance with the applicable sections of ASSE 1037, ANSI/ASME A112.19.2 and Military Specification V-29193. Installation conforms to ADA requirements.

## SPECIFICATIONS (CONTINUED)

### Water Closet

- Floor Mounted
- Vitreous china
- Elongated bowl
- 1-1/2" I.P.S. top spud inlet
- 2-1/4" I.P.S. trapway outlet
- All mounting hardware included
- Integral flushing rim
- Seat not included

## FEATURES

### Automatic

Sloan SOLIS™ solar-powered Flushometers activate via multi-lobular sensor detection to provide the ultimate in sanitary protection and automatic operation. A solar-powered infrared sensor sets the flushing mechanism after the user is detected and completes the flush when the user steps away.

### Functional & Hygienic

Touchless, sensor operation eliminates the need for user contact to help control the spread of infectious diseases. The OPTIMA Plus® Flushometer is provided with an Override Button to allow a "courtesy flush" for individual user comfort.

### Economical

Solar power with back-up batteries provide years of metered flushing to control the use of water and energy. Batteries can be changed without turning off the water.

### Warranty

3 year (limited)



Sloan Valve Company is buying renewable energy certificates to meet 100% of the company's purchased electricity use at its Franklin Park, Illinois facility.



## DESCRIPTION

Complete HET system with Solar-Powered, Sensor Operated OPTIMA Plus® closet Flushometer and vitreous china water closet.

### Flush Cycle

Model WETS 2000.1201-1.28 SOLIS (1.28 gpf/4.84 Lpf)

## ELECTRICAL SPECIFICATIONS

- **Control Circuit**
  - Solid State
  - 6 VDC Input
  - 8 Second Arming Delay
  - 72 hour Sentinel Flush
- **Sloan SOLIS Flush Sensor Type**
  - Active Infrared
- **Sloan SOLIS Flush Sensor Range**
  - Nominal 22" - 42" (559 mm - 1067 mm),
  - Adjustable ± 8" (203 mm)
- **Battery Back-up Type**
  - (4) AA Alkaline
- **Battery Life**
  - 3 Years @ 4,000 flushes/month
- **Indicator Lights**
  - Range adjustment/low battery
- **Operating Pressure**
  - 15 – 100 psi (104 – 689 kPa)
- **Sentinel Flush**
  - Once every 72 Hours after the last flush

## OPERATION



1. A continuous, invisible light beam is emitted from the Sloan SOLIS™ Flush Sensor.



2. As the user enters the beam's effective range, 22 to 42 inches (559 mm to 1067 mm), the beam is reflected into the Scanner Window to activate the Output Circuit. Once activated, the Output Circuit continues in a "hold" mode for as long as the user remains within the effective range of the sensor. If the user stays longer than 65 seconds, a full flush will automatically initiate when the user leaves.



3. When the user steps away from the OPTIMA Plus® Sensor, the circuit waits 3 seconds (to prevent false flushing) then initiates an electrical signal that operates the Solenoid. This initiates the flushing cycle to flush the fixture. The Circuit then automatically resets and is ready for the next user.

## DIMENSIONS/ROUGH-IN

